

MUC-OFF DRY WEATHER LUBE

Page: 1

Compilation date: 02/06/2015

Revision date: 17/01/2019

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: MUC-OFF DRY WEATHER LUBE

Product code: 866-1, 966-1, 832

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Muc-Off Ltd

Unit 1 Concept Office Park, Innovation Close

Poole
Dorset
BH12 4QT

United Kingdom

Tel: (+44) 1202 307790
Email: info@muc-off.com

1.4. Emergency telephone number

Emergency tel: (+44) 1202 307790

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: This product has no classification under CLP.

2.2. Label elements

Label elements:

Precautionary statements: P280: Wear protective gloves.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

MUC-OFF DRY WEATHER LUBE

Page: 2

Hazardous ingredients:

(2-METHOXYMETHYLETHOXY)PROPANOL - REACH registered number(s): 01-2119450011-60

EINECS	CAS	PBT / WEL	CLP Classification	Percent
252-104-2	34590-94	Substance with a Community	-	10-
	-8	workplace exposure limit.		30%

GLYCERINE - REACH registered number(s): 01-2119471987-18

200-289-5	56-81-5	Substance with a Community	_	10-
		workplace exposure limit.		30%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to

skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: * Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: * No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: * Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to

prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

MUC-OFF DRY WEATHER LUBE

Page: 3

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

(2-METHOXYMETHYLETHOXY)PROPANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	50ppm(sk)	-	-	-

GLYCERINE

UK	10ma/m2			
l OK	Tumg/m3	-	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

MUC-OFF DRY WEATHER LUBE

Page: 4

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Emulsion
Colour: Off-white
Odour: Pleasant
Evaporation rate: Moderate

Oxidising: Not applicable.

Solubility in water: Soluble

Viscosity: Viscous

Boiling point/range°C: 100 Melting point/range°C: <0

Flammability limits %: lower: No data available. upper: No data available.

Flash point °C: >93 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: >150 Vapour pressure: No data available.

Relative density: 1.050 pH: 7.50

VOC g/I: Not applicable.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage

conditions. Decomposition may occur on exposure to conditions or materials

listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

MUC-OFF DRY WEATHER LUBE

Page: 5

11.1. Information on toxicological effects

Hazardous ingredients:

(2-METHOXYMETHYLETHOXY)PROPANOL

DERMAL	RBT	LD50	9150	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

GLYCERINE

ORAL	RAT	IDEO	23000	ma/ka
UKAL	IKAI	LD50	23000	i iiiu/ku

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: * No data available.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

(2-METHOXYMETHYLETHOXY)PROPANOL

DAPHNIA	48H EC50	1919	mg/l
FISH	96H LC50	>1000	mg/l
GREEN ALGA (Selenastrum capricornutum)	96H ErC50	>969	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

MUC-OFF DRY WEATHER LUBE

Page: 6

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised

disposal company.

NB: The user's attention is drawn to the possible existence of regional or

national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixt

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission

Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Legal disclaimer: The above information is believed to be correct but does not purport to be

all inclusive and shall be used only as a guide. This company shall not be

held liable for any damage resulting from handling or from contact with the $% \left(1\right) =\left(1\right) \left(1\right)$

above product.